

View Online at <https://aerobasegroup.com/nsn/5930-00-192-2839>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Body Length:**

Between 1.795 inches and 1.825 inches

**Body Width:**

Between 0.625 inches and 0.655 inches

**Body Height:**

Between 0.625 inches and 0.655 inches

**Unthreaded Mounting Hole Diameter:**

0.145 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.245 inches and 0.255 inches

**Actuator Height:**

0.300 inches

**Actuator Free Position Height:**

Between 0.690 inches and 0.750 inches

**Maximum Voltage Rating In Volts:**

250.0 ac

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, double make, momentary action single switch unit

**Switch Release Force:**

3.0 ounces

**Switch Actuating Force:**

20.0 ounces

**Actuator Movement:**

Between 0.050 pretravel inches and 0.050 overtravel inches and 0.010 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive ac

**Terminal Type And Quantity:**

2 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0