NSN 5930-00-194-7082

Rotary Switch - Page 1 of 2

Thread Class:

Thread Length:

2a single mounting facility



View Online at https://aerobasegroup.com/nsn/5930-00-194-7082

0.312 inches single mounting facility **Overall Length:** 3.562 inches **Overall Height:** 1.937 inches **Overall Width:** 2.312 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.469 inches single actuator **Overall Diameter:** 1.937 inches **Individual Section Quantity:** 3 **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Pole Quantity:** 1 each section rear **Throw Quantity:** 20 each section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 23 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Makes before breaks each section rear **Switch Actuator Positioning Increment:** 15.0 degrees single actuator **Switch Actuator Stop Device Type:**

Adjustable stop single actuator

NSN 5930-00-194-7082

Rotary Switch - Page 2 of 2



Contact Load Current Rating

500.0 milliamperes resistive load ac at sea level

Special Features:

Aluminum shield 3.750in wide 3.375in high between section one and section two

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0