NSN 5930-00-194-9139

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-194-9139 **Body Style:** Hole mounted **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.375 inches **Body Length:** 0.781 inches **Body Width:** 0.250 inches **Body Height:** 0.356 inches **Unthreaded Mounting Hole Diameter:** 0.088 inches **Actuator Style:** Leaf **Actuator Width:** 0.140 inches **Actuator Free Position Height:** 0.605 inches **Maximum Voltage Rating In Volts:** 250.0 ac and 30.0 dc Inclosure Type: Fully enclosed **Mounting Method:** Threaded hole **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Switch Release Force:** 7.0 grams **Switch Actuating Force:** 40.0 grams **Actuator Movement:** Between 0.085 pretravel inches and 0.011 overtravel inches and 0.019 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac **Terminal Type And Quantity:** 3 turret Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5930-00-194-9139

Sensitive Switch - Page 2 of 2



Fiig:

A053a0