NSN 5930-00-195-3241

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-195-3241

| Hazardous Locations/environmental Protection: |
|---|
| Explosion proof |
| Overall Length: |
| 1.300 inches |
| Body Diameter: |
| 0.670 inches |
| Body Height: |
| 1.230 inches |
| Distance Between Mounting Facility Centers: |
| 1.080 inches |
| Tempurature Sensing Element Type: |
| Internal sensor |
| Mounting Method: |
| Bracket |
| Features Provided: |
| Hermetically sealed case |
| Contact Action Stimulus: |
| Decrease |
| Mounting Facility Pattern: |
| Two position in-line |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, both positions maintained |
| Terminal Type: |
| Connector, receptacle |
| Contact Load Current Rating: |
| 0.5 amperes inductive load single voltage |
| Contact Adjustability: |
| Deactuation point not adjustable and actuation point not adjustable |
| Contact Stimulus Rating: |
| 127.00 actuation point degrees fahrenheit and 135.00 deactuation point degrees fahrenheit |
| Contact Voltage Rating In Volts: |
| 28.0 dc at sea level single voltage |
| Media For Which Designed: |
| Gas |
| Style Designator: |
| Disc w/flange |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

Yes - demil/mli

NSN 5930-00-195-3241

Thermostatic Switch - Page 2 of 2



Fiig:

A048b0