## NSN 5930-00-195-3253

Sensitive Switch - Page 1 of 2

**Body Style:**Hole mounted

0.875 inches



View Online at https://aerobasegroup.com/nsn/5930-00-195-3253

**Center To Center Distance Between Mounting Facilities Parallel To Length:** 

Body Length:
1.094 inches
Body Width:
0.406 inches
Body Height:
0.625 inches
Unthreaded Mounting Hole Diameter:
0.114 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.406 inches
Actuator Length:
0.406 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
0.312 inches
Actuator Roller Diameter:
0.188 inches
Actuator Roller Width:
0.188 inches
Maximum Voltage Rating In Volts:
250.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
1.0 ounces
Switch Actuating Force:
14.0 ounces
Actuator Movement:
Between 0.062 pretravel inches and 0.050 overtravel inches and 0.016 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive ac
Terminal Type And Quantity:
3 tab, solder lug

## NSN 5930-00-195-3253

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0