

View Online at <https://aerobasegroup.com/nsn/5930-00-195-3253>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Body Length:

1.094 inches

Body Width:

0.406 inches

Body Height:

0.625 inches

Unthreaded Mounting Hole Diameter:

0.114 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Actuator Length:

0.406 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

0.312 inches

Actuator Roller Diameter:

0.188 inches

Actuator Roller Width:

0.188 inches

Maximum Voltage Rating In Volts:

250.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

14.0 ounces

Actuator Movement:

Between 0.062 pretravel inches and 0.050 overtravel inches and 0.016 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0