# NSN 5930-00-195-8776

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-195-8776

# Thread Length:

0.437 inches single mounting facility

# Hazardous Locations/environmental Protection:

Explosion proof

# **Overall Length:**

5.013 inches

### First Flat Length:

0.250 inches single actuator

#### Flat Height:

0.216 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.437 inches single actuator

#### **Overall Diameter:**

Between 1.000 inches and 1.306 inches

#### **Nonturn Device Radius:**

0.375 inches at 3: 00 o'clock

# Individual Section Quantity:

10

Nonturn Device Type:

Tab at 3: 00 o'clock

# **Operating Tempurature Range:**

-65.0/+85.0 degrees celsius

# Switch Contact Basic Design:

Nonpile-up symmetrical

# Pole Quantity:

1 each section front

# Throw Quantity:

10 each section rear

# **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

# **Contact Voltage Rating In Volts:**

28.0 dc at sea level

# Shaft Flat/slot Angular Location:

216.0 degrees from nonturn device single actuator

# **Rotor Through Connection Quantity:**

1 each section

#### **Switch Actuator Indexing Position Quantity:**

10 single actuator

# NSN 5930-00-195-8776

Rotary Switch - Page 2 of 2



Shaft Type:

Round, flatted single actuator

**Terminal Type:** 

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

**Detent Rotational Torque Range:** 

+1.750/+7.000 inch-pounds single actuator

**Contact Load Current Rating:** 

75.0 milliamperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

#### **Test Data Document:**

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Thread Series Designator:**

Unef single mounting facility

Specification Data:

81349-mil-s-3786/4 government specification

Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A052b0