## NSN 5930-00-195-9428

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-195-9428

Body Style: Hole mount  Overall Length: 2.092 inches  Center To Center Distance Between Mounting Facilities Parallel To Width: 0.709 inches
Overall Length: 2.092 inches Center To Center Distance Between Mounting Facilities Parallel To Width:
2.092 inches  Center To Center Distance Between Mounting Facilities Parallel To Width:
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.709 inches
0.700 mones
Overall Height:
0.787 inches
Overall Width:
0.905 inches
Body Length:
1.305 inches
Body Width:
0.905 inches
Body Height:
0.315 inches
Actuator Length:
0.130 inches
Actuator Style:
Rectangular
Actuator Width:
0.130 inches
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Nimitz class cvn, spruance class d (963) , general purpose electronic test equipment
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded hole
Nonpile-up Contact Arrangement:
4 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
1.000 amperes resistive dc and 450.000 milliamperes resistive ac
Precious Material And Location:
Terminal surfaces and contacts silver
Terminal Type And Quantity:
12 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5930-00-195-9428

Push Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0