NSN 5930-00-197-3838

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-197-3838

Body Style:				
Panel mounted				
Hazardous Locations/environmental Protection:				
Explosion proof and humidity resistant				
Overall Length:				
3.706 inches				
Overall Height:				
0.750 inches				
Overall Width:				
0.750 inches				
Body Width:				
0.750 inches				
Body Height:				
0.750 inches				
Case Material:				
Metal				
Actuator Length:				
0.620 inches				
Actuator Style:				
Rectangular				
Actuator Height:				
0.100 inches				
Actuator Width:				
0.620 inches				
Actuator Color:				
Green single actuator				
Illuminated Actuator Color:				
Green single actuator				
Actuator Inscription:				
B single actuator				
Maximum Voltage Rating In Volts:				
115.0 ac and 28.0 dc				
End Application:				
Aircraft, sof (ac-130h, mc-130h, ec-130e, hc-130)				
Mounting Surface To Terminal End Distance:				
3.140 inches				
Inclosure Type:				
Fully enclosed				
Mounting Method:				
Panel				
Features Provided:				

Features Provided

Full display lens and holding solenoid

NSN 5930-00-197-3838

Push Switch - Page 2 of 2



Nonpile-up Contact Arrangement:

4 two circuit, double break/double make, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac and 1.000 amperes lamp ac

D!	NA-1:	AI I	
Precious	Materiai	And I	Location:

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0