NSN 5930-00-197-3846

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Explosion proof and humidity resistant

Body Style:Panel mounted

Overall Length: 3.706 inches Overall Height: 0.750 inches



View Online at https://aerobasegroup.com/nsn/5930-00-197-3846

| Overall Width: |
|---|
| 0.750 inches |
| Body Width: |
| 0.750 inches |
| Body Height: |
| 0.750 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| 0.620 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.100 inches |
| Actuator Width: |
| 0.620 inches |
| Actuator Color: |
| Green single actuator |
| Illuminated Actuator Color: |
| Green single actuator |
| Actuator Inscription: |
| C single actuator |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Mounting Surface To Terminal End Distance: |
| 3.140 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |
| Full display lens and holding solenoid |
| Nonpile-up Contact Arrangement: |
| 4 two circuit, double break/double make, both positions maintained single switch unit |
| |
| |

NSN 5930-00-197-3846

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac and 1.000 amperes lamp ac

| P | racions | Matarial | And | Location: |
|---|---------|----------|------|-----------|
| _ | recious | wateriai | Allu | LOCALION. |

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0