# NSN 5930-00-197-3925

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-197-3925

### **Thread Class:**

2a single mounting facility

### Thread Length:

0.375 inches single mounting facility

## **Overall Length:**

3.126 inches

#### **Overall Height:**

2.313 inches

#### **Overall Width:**

1.968 inches

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

2.250 inches single actuator

#### **Nonturn Device Radius:**

## 0.531 inches at 9:00 o'clock

#### Individual Section Quantity:

2

#### Nonturn Device Type:

Tab at 9: 00 o'clock

### Switch Contact Basic Design:

Nonpile-up symmetrical

#### Pole Quantity:

1 each section rear

#### **Throw Quantity:**

23 each section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### Contact Voltage Rating In Volts:

28.0 dc at sea level

#### Switch Actuator Indexing Position Quantity:

24 single actuator

## Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Makes before breaks each section rear

#### Switch Actuator Positioning Increment:

15.0 degrees single actuator

# NSN 5930-00-197-3925

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type: Adjustable stop single actuator **Contact Load Current Rating:** 1.5 amperes resistive load dc at sea level Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0