NSN 5930-00-197-4529

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-197-4529

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

1.865 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.188 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

1.085 inches single actuator and 1.115 inches single actuator

Overall Diameter:

1.190 inches

Nonturn Device Radius:

0.375 inches at 3: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3: 00 o'clock

Operating Tempurature Range:

-65.0/+85.0 degrees celsius

End Application:

Tarawa class lha, virginia class cgn (41), ticonderoga class cg (47), spruance class dd (963), oliver perry class ffg, kidd class ddg, wasp class lhe, forrestal class cv.

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

3 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

330.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

3 single actuator

NSN 5930-00-197-4529 Rotary Switch - Page 2 of 2



Shaft Type:
Round, flatted single actuator
Criticality Code Justification:
Feat
Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes single section rear
Switch Actuator Positioning Increment:
30.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
200.0 milliamperes resistive load dc at sea level and 20.0 milliamperes inductive load dc at sea level
Special Features:
Weapon system essential
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A052b0