## NSN 5930-00-197-4686

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-197-466
Thread Class:
2b single mounting facility
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
3.337 inches
Overall Height:
2.500 inches
First Flat Length:
0.750 inches single actuator
Flat Height:
0.219 inches single actuator
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
1.125 inches single actuator
Individual Section Quantity:
5
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
A
Longest Horizontal Distance Between Mounting Centers:
1.641 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
1.641 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section rear
Throw Quantity:
2 each section rear
Mounting Method:
Threaded hole single mounting facility
Features Provided:
Actuator knob
Thready Qty Per Inch (tpi):
24 single mounting facility
Thread Size:

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:** 

125.0 ac at sea level

## NSN 5930-00-197-4686

Rotary Switch - Page 2 of 2



Mounting Facility Pattern:
Four position rectangular single mounting facility
<b>Switch Actuator Indexing Position Quantity:</b>
2 single actuator
Shaft Type:
Round, flatted, threaded hole single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
10.0 amperes resistive load ac at sea level
Style Designator:
Tap, circuit selector
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A052b0