NSN 5930-00-197-4690

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-197-4690

| Body Style: |
|--|
| Hole mounted |
| Overall Length: |
| 0.781 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.375 inches |
| Overall Height: |
| 0.694 inches |
| Overall Width: |
| 0.250 inches |
| Body Length: |
| 0.781 inches |
| Body Width: |
| 0.250 inches |
| Body Height: |
| 0.359 inches |
| Case Material: |
| Plastic |
| Unthreaded Mounting Hole Diameter: |
| Between 0.087 inches and 0.090 inches |
| Actuator Length: |
| 0.406 inches |
| Actuator Style: |
| Leaf |
| Actuator Free Position Height: |
| 0.350 inches |
| Maximum Voltage Rating In Volts: |
| 250.0 ac and 30.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary single switch unit |
| Switch Actuating Force: |
| 8.0 grams |
| Actuator Movement: |
| Between 0.438 pretravel inches and 0.050 overtravel inches and 0.050 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 3.000 amperes resistive dc and 5.000 amperes resistive ac |
| Precious Material And Location: |
| Terminal surfaces and contacts silver |
| Terminal Type And Quantity: |
| 3 quick disconnect, male |

NSN 5930-00-197-4690

Sensitive Switch - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0