## NSN 5930-00-199-6015

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-199-6015

Inside Diameter:
0.250 inches single connection
Overall Length:
2.563 inches
Overall Height:
7.313 inches
Overall Width:
3.250 inches
Body Height:
4.625 inches
Unthreaded Mounting Hole Diameter:
0.219 inches
Longest Horizontal Distance Between Mounting Centers:
1.625 inches
Longest Vertical Distance Between Mounting Centers:
1.375 inches
Pressure Switch Type:
Gage
Mounting Method:
Base and unthreaded hole
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Increase
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position diagonal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Tab w/screw
Contact Load Current Rating:
5.0 amperes resistive load second voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+50.00/+650.00 actuation point pounds per square inch and +37.00/+500.00 deactuation point pounds per square inch

**Contact Adjustment Type:** 

Internal deactuation point screw and internal actuation point screw

## NSN 5930-00-199-6015

Pressure Switch - Page 2 of 2



## Contact Voltage Rating In Volts: 600.0 ac at sea level first voltage Pressure Connector Type: Plain, threaded internal single connection Media For Which Designed: Gas or liquid Style Designator: Rectangular Thread Series Designator: Npt single pressure connection Shelf Life: N/a Unit Of Measure: --Demilitarization:

No Fiig: A048b0