

View Online at <https://aerobasegroup.com/nsn/5930-00-199-6015>

Inside Diameter:

0.250 inches single connection

Overall Length:

2.563 inches

Overall Height:

7.313 inches

Overall Width:

3.250 inches

Body Height:

4.625 inches

Unthreaded Mounting Hole Diameter:

0.219 inches

Longest Horizontal Distance Between Mounting Centers:

1.625 inches

Longest Vertical Distance Between Mounting Centers:

1.375 inches

Pressure Switch Type:

Gage

Mounting Method:

Base and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+50.00/+650.00 actuation point pounds per square inch and +37.00/+500.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Voltage Rating In Volts:

600.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0