# NSN 5930-00-199-7633

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-199-7633

#### **Body Style:**

Hole mounted

#### **Overall Length:**

1.625 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

#### **Overall Height:**

1.518 inches

#### **Overall Width:**

0.277 inches

#### **Body Length:**

1.203 inches

#### Body Width:

0.277 inches

## Body Height:

0.828 inches

#### ----

Case Material:

Plastic

#### **Unthreaded Mounting Hole Diameter:**

0.172 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Height:

0.625 inches

#### Actuator Style:

Roller arm

#### **Actuator Free Position Height:**

0.791 inches

#### Maximum Voltage Rating In Volts:

250.0 ac

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Unthreaded hole

#### Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

#### Switch Release Force:

1.0 ounces

#### Switch Actuating Force:

Between 3.0 ounces and 12.0 ounces

#### **Actuator Movement:**

Between 0.031 pretravel inches and 0.025 overtravel inches and 0.008 differential inches

### Contact Load Current Rating At Maximum Rated Voltage:

6.000 amperes resistive ac

# NSN 5930-00-199-7633

Sensitive Switch - Page 2 of 2



### Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0