NSN 5930-00-199-8160

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-199-8160

Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.875 inches
Body Length:
1.094 inches
Body Width:
0.400 inches
Body Height:
0.625 inches
Unthreaded Mounting Hole Diameter:
0.114 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.406 inches
Actuator Length:
1.000 inches
Actuator Style:
Leaf
Actuator Width:
0.170 inches
Actuator Free Position Height:
0.319 inches
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
1.0 ounces
Switch Actuating Force:
8.0 ounces
Actuator Movement:
Between 0.125 pretravel inches and 0.090 overtravel inches and 0.050 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 10.000 amperes resistive ac
Terminal Type And Quantity:
3 tab w/screw
Shelf Life:
N/a
Unit Of Measure:

-

NSN 5930-00-199-8160

Sensitive Switch - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A053a0