

View Online at <https://aerobasegroup.com/nsn/5930-00-200-9104>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

6.875 inches

**Overall Height:**

10.016 inches

**Overall Width:**

3.500 inches

**Body Height:**

7.875 inches

**Unthreaded Mounting Hole Diameter:**

0.187 inches

**Capillary Tube Length:**

120.0 inches

**Bulb Length:**

2.687 inches

**Bulb Diameter:**

0.984 inches

**Longest Horizontal Distance Between Mounting Centers:**

5.125 inches

**Shortest Horizontal Distance Between Mounting Centers:**

1.312 inches

**Intermediate Horizontal Distance Between Mounting Centers:**

2.500 inches

**Longest Vertical Distance Between Mounting Centers:**

7.156 inches

**Temperature Sensing Element Type:**

Capillary tube-bulb

**Mounting Method:**

Unthreaded hole

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Four position parallelogram

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

500.0 milliamperes resistive load fourth voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+50.00/+424.00 actuation point degrees fahrenheit and +50.00/+300.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External deactuation point knob with scale and external actuation point knob with scale

**Contact Voltage Rating In Volts:**

250.0 dc at sea level third voltage

**Media For Which Designed:**

Gas

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0