

View Online at <https://aerobasegroup.com/nsn/5930-00-200-9303>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Body Length:

Between 1.079 inches and 1.109 inches

Body Width:

0.400 inches

Body Height:

Between 0.610 inches and 0.640 inches

Unthreaded Mounting Hole Diameter:

0.114 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Actuator Length:

0.110 inches

Actuator Style:

Rectangular

Actuator Height:

0.110 inches

Actuator Width:

0.165 inches

Actuator Free Position Height:

0.640 inches

Maximum Voltage Rating In Volts:

250.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

5.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

12.0 ounces

Actuator Movement:

Between 0.047 pretravel inches and 0.040 overtravel inches and 0.006 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac

Special Features:

Item must comply with rqmt of desc production standard no. L01049

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0