

View Online at <https://aerobasegroup.com/nsn/5930-00-200-9303>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.875 inches

**Body Length:**

Between 1.079 inches and 1.109 inches

**Body Width:**

0.400 inches

**Body Height:**

Between 0.610 inches and 0.640 inches

**Unthreaded Mounting Hole Diameter:**

0.114 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.406 inches

**Actuator Length:**

0.110 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.110 inches

**Actuator Width:**

0.165 inches

**Actuator Free Position Height:**

0.640 inches

**Maximum Voltage Rating In Volts:**

250.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

5.0 ounces

**Criticality Code Justification:**

Feat

**Switch Actuating Force:**

12.0 ounces

**Actuator Movement:**

Between 0.047 pretravel inches and 0.040 overtravel inches and 0.006 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive ac

**Special Features:**

Item must comply with rqmt of desc production standard no. L01049

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0