## NSN 5930-00-200-9326

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-200-9326

Overall Length:
1.578 inches
Overall Height:
5.125 inches
Body Diameter:
0.625 inches
Body Height:
3.500 inches
Unthreaded Mounting Hole Diameter:
0.221 inches
End Application:
$We apon \ systems-aircraft, \ her cules \ c-130; \ engine, \ aircraft, \ t56-a-7/15 \ (c-130b/e/h/n/p); \ aircraft, \ sof (ac-130h, \ mc-130h, \ ec-130e, \ ac-130h, \ mc-130h, \ ec-130e, \ ac-130h, \ ec-130e, \ ac-130h, \ ec-130e, \ ec-130e$
hc-130); aircraft, awacs, e-3a; aircraft, statolifter c-135; u-2 airframe
Tempurature Sensing Element Type:
Expanding shell
Mounting Facility Circle Radius:
0.625 inches
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 1000.0 degrees fahrenheit
Mounting Method:
Flange and unthreaded hole
Features Provided:
Hermetically sealed case and internally grounded
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Three position circular
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Criticality Code Justification:
Feat
Terminal Type:
Threaded stud
Contact Load Current Rating:
3.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point adjustable, preset and actuation point adjustable, preset

### **Contact Adjustment Range:**

+135.00/+1000.00 actuation point degrees fahrenheit and +135.00/+1000.00 deactuation point degrees fahrenheit

#### **Contact Adjustment Type:**

Internal deactuation point screw and internal actuation point screw

#### **Contact Stimulus Rating:**

300.00 actuation point degrees fahrenheit and 280.00 deactuation point degrees fahrenheit

# **NSN 5930-00-200-9326** Thermostatic Switch - Page 2 of 2



Contact Voltage Rating In Volts:
28.0 dc at sea level single voltage
Special Features:
Weapon system essential
Media For Which Designed:
Gas or liquid
Style Designator:
Disc w/flange
Test Data Document:
81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-s-24236/15 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A048b0