# NSN 5930-00-201-3345

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-201-3345

# **Thread Class:**

2a single mounting facility

# Thread Length:

0.375 inches single mounting facility

# **Overall Length:**

1.781 inches

#### **Overall Height:**

1.875 inches

#### **Overall Width:**

1.625 inches

#### First Flat Length:

0.500 inches single actuator

#### Flat Height:

0.219 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

# Shaft Length:

1.125 inches single actuator

# Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up symmetrical

# **Pole Quantity:**

2 single section rear

#### **Throw Quantity:**

4 single section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### Thread Size:

0.375 inches single mounting facility

#### Contact Voltage Rating In Volts:

28.0 dc at sea level

#### Switch Actuator Indexing Position Quantity:

4 single actuator

#### Shaft Type:

Round, flatted single actuator

#### **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Breaks before makes single section rear

# Switch Actuator Positioning Increment:

20.0 degrees single actuator

# NSN 5930-00-201-3345

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type:

Fixed stop single actuator

# **Contact Load Current Rating:**

500.0 milliamperes resistive load ac at sea level

# **Precious Material And Location:**

Contacts and rotor blade surfaces silver

**Precious Material:** 

Silver

# Style Designator:

Circular wafer, bushing mount

# Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

#### Unit Of Measure:

---

# Demilitarization:

No

# Fiig:

A052b0