

View Online at <https://aerobasegroup.com/nsn/5930-00-201-3394>

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

4.000 inches

**Shaft Length:**

1.250 inches single actuator

**Overall Diameter:**

2.812 inches

**Individual Section Quantity:**

3

**Longest Horizontal Distance Between Mounting Centers:**

1.812 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Facility Circle Radius:**

0.906 inches single mounting facility

**Mounting Method:**

Threaded bushing single mounting facility

**Contact Voltage Rating In Volts:**

125.0 ac at sea level

**Mounting Facility Pattern:**

Four position diamond single mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Rectangular/square, threaded hole single actuator

**Square Shaft Size:**

0.250 inches single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Contact Load Current Rating:**

10.0 amperes resistive load ac at sea level

**Style Designator:**

Tap, circular, bushing mount

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0