

View Online at <https://aerobasegroup.com/nsn/5930-00-201-3394>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

4.000 inches

Shaft Length:

1.250 inches single actuator

Overall Diameter:

2.812 inches

Individual Section Quantity:

3

Longest Horizontal Distance Between Mounting Centers:

1.812 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Facility Circle Radius:

0.906 inches single mounting facility

Mounting Method:

Threaded bushing single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Four position diamond single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Square Shaft Size:

0.250 inches single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0