NSN 5930-00-201-3402

Rotary Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-201-3402

| Hazardous Locations/environmental Protection: |
|---|
| Watertight |
| Shaft Diameter: |
| 0.250 inches single actuator |
| Shaft Length: |
| 0.938 inches single actuator |
| Individual Section Quantity: |
| 1 |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 1 single section front |
| Throw Quantity: |
| 2 single section front |
| Mounting Method: |
| Base single mounting facility |
| Features Provided: |
| Metallic inclosure |
| Contact Voltage Rating In Volts: |
| 250.0 dc at sea level |
| Switch Actuator Indexing Position Quantity: |
| 2 single actuator |
| Shaft Type: |
| Round single actuator |
| Terminal Type: |
| Tab, solder lug |
| Contact Switching Action: |
| Breaks before makes single section front |
| Switch Actuator Positioning Increment: |
| 90.0 degrees single actuator |
| Contact Load Current Rating: |
| 10.0 amperes resistive load dc at sea level |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A052b0 |