## NSN 5930-00-201-3586

Lever Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-201-3586 **Thread Class:** 2b **Body Style:** Hole mounted **Overall Length:** 5.094 inches Center To Center Distance Between Mounting Facilities Parallel To Width: 0.816 inches **Overall Height:** 1.438 inches **Overall Width:** 1.125 inches **Body Length:** 3.500 inches **Body Width:** 1.125 inches **Body Height:** 1.438 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.124 inches **Actuator Style:** Round **Actuator Height:** 1.594 inches **Actuator Position-action Relationship:** Up position maintained and down position momentary and center position maintained **Actuator Position-locking Relationship:** Up position locked in and down position locked out and center position locked in **Actuator Color:** Black single actuator **Maximum Voltage Rating In Volts:** 110.0 ac **Inclosure Type:** Uninclosed **Mounting Method:** Threaded hole Thready Qty Per Inch (tpi): 40 **Pile-up Contact Form Arrangement:** 

2c 1st position **Thread Size:** 

0.112 inches

## NSN 5930-00-201-3586

Lever Switch - Page 2 of 2

No Fiig: A053a0



Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive ac
Precious Material And Location:
Contacts silver
Thread Series Designator:
Unc
Terminal Type And Quantity:
14 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: