NSN 5930-00-201-3587

Lever Switch - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5930-00-201-3587

| Thread Olara |
|--|
| Thread Class: |
| 2b |
| Body Style: |
| Hole mounted |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.531 inches |
| Body Width: |
| 0.844 inches |
| Body Height: |
| 1.188 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 0.812 inches |
| Actuator Position-action Relationship: |
| Up position maintained and down position maintained and center position maintained |
| Actuator Position-locking Relationship: |
| Up position locked in and down position locked in and center position locked in |
| Maximum Voltage Rating In Volts: |
| 110.0 ac |
| Inclosure Type: |
| Uninclosed |
| Mounting Method: |
| Threaded hole |
| Thready Qty Per Inch (tpi): |
| 40 |
| Pile-up Contact Form Arrangement: |
| 2c 2nd position |
| Thread Size: |
| 0.112 inches |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 5.000 amperes resistive ac |
| Thread Series Designator: |
| Unc |
| Terminal Type And Quantity: |
| 12 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A053a0 |
| |