

View Online at <https://aerobasegroup.com/nsn/5930-00-201-3817>

First Flat Length:

0.375 inches single actuator

Flat Height:

0.180 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.562 inches single actuator

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.250 inches 2nd mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

2 single section rear

Mounting Method:

Threaded bushing 1st mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Contact Voltage Rating In Volts:

250.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Two position in-line 2nd mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

48.0 degrees single actuator

Contact Load Current Rating:

1.0 amperes resistive load highest ac voltage rating at sea level

Special Features:

Two 6-32 tapped mtg holes 1-1/4 in. C to c

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0