NSN 5930-00-201-4737

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-201-4737

Thread Class:

2a single mounting facility

Thread Length:

0.469 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.844 inches

First Flat Length:

0.469 inches single actuator

Flat Height:

0.188 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.000 inches single actuator

Overall Diameter:

2.188 inches

Individual Section Quantity:

4

Knob Manufacturer Code:

27191

Knob Manufacturer Part Number:

53-635

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

5 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.469 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted single actuator

NSN 5930-00-201-4737

Rotary Switch - Page 2 of 2



Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Contact Load Current Rating:
10.0 amperes resistive load ac at sea level
Style Designator:
Tap, circular, bushing mount
Thread Series Designator:
Uns single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A052b0