## NSN 5930-00-201-5057

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-201-5057

Maximum Voltage Rating In Volts: 230.0 ac and 250.0 dc Inclosure Type: Fully enclosed Mounting Method: Integral Nonpile-up Contact Arrangement: 1 pole, single throw, double make, both positions maintained single switch unit Switch Release Force: 4.0 ounces Switch Actuating Force: 27.0 ounces Actuator Movement: 0.040 pretravel inches and 0.085 overtravel inches Contact Load Current Rating At Maximum Rated Voltage: 250.000 milliamperes resistive dc and 25.000 amperes resistive ac Terminal Type And Quantity: 2 screw Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Inclosure Type: Fully enclosed Mounting Method: Integral Nonpile-up Contact Arrangement: 1 pole, single throw, double make, both positions maintained single switch unit Switch Release Force: 4.0 ounces Switch Actuating Force: 27.0 ounces Actuator Movement: 0.040 pretravel inches and 0.085 overtravel inches Contact Load Current Rating At Maximum Rated Voltage: 250.000 milliamperes resistive dc and 25.000 amperes resistive ac Terminal Type And Quantity: 2 screw Shelf Life: N/a Unit Of Measure: Demilitarization: No	laximum Voltage Rating In Volts:
Fully enclosed  Mounting Method: Integral  Nonpile-up Contact Arrangement: 1 pole, single throw, double make, both positions maintained single switch unit  Switch Release Force: 4.0 ounces  Switch Actuating Force: 27.0 ounces  Actuator Movement: 0.040 pretravel inches and 0.085 overtravel inches  Contact Load Current Rating At Maximum Rated Voltage: 250.000 milliamperes resistive dc and 25.000 amperes resistive ac  Terminal Type And Quantity: 2 screw  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No	30.0 ac and 250.0 dc
Mounting Method: Integral Nonpile-up Contact Arrangement: 1 pole, single throw, double make, both positions maintained single switch unit Switch Release Force: 4.0 ounces Switch Actuating Force: 27.0 ounces Actuator Movement: 0.040 pretravel inches and 0.085 overtravel inches Contact Load Current Rating At Maximum Rated Voltage: 250.000 milliamperes resistive dc and 25.000 amperes resistive ac Terminal Type And Quantity: 2 screw Shelf Life: N/a Unit Of Measure: Demilitarization: No	nclosure Type:
Integral  Nonpile-up Contact Arrangement:  1 pole, single throw, double make, both positions maintained single switch unit  Switch Release Force:  4.0 ounces  Switch Actuating Force:  27.0 ounces  Actuator Movement:  0.040 pretravel inches and 0.085 overtravel inches  Contact Load Current Rating At Maximum Rated Voltage:  250.000 milliamperes resistive dc and 25.000 amperes resistive ac  Terminal Type And Quantity:  2 screw  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	ully enclosed
Nonpile-up Contact Arrangement:  1 pole, single throw, double make, both positions maintained single switch unit Switch Release Force:  4.0 ounces Switch Actuating Force:  27.0 ounces Actuator Movement:  0.040 pretravel inches and 0.085 overtravel inches Contact Load Current Rating At Maximum Rated Voltage:  250.000 milliamperes resistive dc and 25.000 amperes resistive ac Terminal Type And Quantity:  2 screw Shelf Life: N/a Unit Of Measure: Demilitarization: No	lounting Method:
1 pole, single throw, double make, both positions maintained single switch unit  Switch Release Force: 4.0 ounces  Switch Actuating Force: 27.0 ounces  Actuator Movement: 0.040 pretravel inches and 0.085 overtravel inches  Contact Load Current Rating At Maximum Rated Voltage: 250.000 milliamperes resistive dc and 25.000 amperes resistive ac  Terminal Type And Quantity: 2 screw  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No	ntegral
Switch Release Force: 4.0 ounces Switch Actuating Force: 27.0 ounces Actuator Movement: 0.040 pretravel inches and 0.085 overtravel inches Contact Load Current Rating At Maximum Rated Voltage: 250.000 milliamperes resistive dc and 25.000 amperes resistive ac Terminal Type And Quantity: 2 screw Shelf Life: N/a Unit Of Measure: Demilitarization: No	onpile-up Contact Arrangement:
4.0 ounces  Switch Actuating Force:  27.0 ounces  Actuator Movement:  0.040 pretravel inches and 0.085 overtravel inches  Contact Load Current Rating At Maximum Rated Voltage:  250.000 milliamperes resistive dc and 25.000 amperes resistive ac  Terminal Type And Quantity:  2 screw  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	pole, single throw, double make, both positions maintained single switch unit
Switch Actuating Force:  27.0 ounces  Actuator Movement:  0.040 pretravel inches and 0.085 overtravel inches  Contact Load Current Rating At Maximum Rated Voltage:  250.000 milliamperes resistive dc and 25.000 amperes resistive ac  Terminal Type And Quantity:  2 screw  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	witch Release Force:
27.0 ounces  Actuator Movement:  0.040 pretravel inches and 0.085 overtravel inches  Contact Load Current Rating At Maximum Rated Voltage:  250.000 milliamperes resistive dc and 25.000 amperes resistive ac  Terminal Type And Quantity:  2 screw  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	.0 ounces
Actuator Movement:  0.040 pretravel inches and 0.085 overtravel inches  Contact Load Current Rating At Maximum Rated Voltage: 250.000 milliamperes resistive dc and 25.000 amperes resistive ac  Terminal Type And Quantity: 2 screw  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No	witch Actuating Force:
0.040 pretravel inches and 0.085 overtravel inches  Contact Load Current Rating At Maximum Rated Voltage: 250.000 milliamperes resistive dc and 25.000 amperes resistive ac  Terminal Type And Quantity: 2 screw  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No	7.0 ounces
Contact Load Current Rating At Maximum Rated Voltage:  250.000 milliamperes resistive dc and 25.000 amperes resistive ac  Terminal Type And Quantity:  2 screw  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	ctuator Movement:
250.000 milliamperes resistive dc and 25.000 amperes resistive ac  Terminal Type And Quantity: 2 screw  Shelf Life: N/a Unit Of Measure: Demilitarization: No	.040 pretravel inches and 0.085 overtravel inches
Terminal Type And Quantity:  2 screw  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	ontact Load Current Rating At Maximum Rated Voltage:
2 screw  Shelf Life: N/a Unit Of Measure: Demilitarization: No	50.000 milliamperes resistive dc and 25.000 amperes resistive ac
Shelf Life: N/a Unit Of Measure: Demilitarization: No	erminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: No	screw
Unit Of Measure: Demilitarization: No	helf Life:
Demilitarization:	l/a
No	nit Of Measure:
No	
	emilitarization:
Fiia:	lo
<b>5</b>	iig:
A053a0	053a0