

View Online at <https://aerobasegroup.com/nsn/5930-00-201-7443>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Waterproof

**Bushing Length:**

0.294 inches

**Body Length:**

0.827 inches

**Body Width:**

0.492 inches

**Body Height:**

0.625 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.118 inches

**Actuator Height:**

0.413 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, three positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 2.000 amperes inductive dc and 3.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

12 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0