

View Online at <https://aerobasegroup.com/nsn/5930-00-201-7443>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Waterproof

Bushing Length:

0.294 inches

Body Length:

0.827 inches

Body Width:

0.492 inches

Body Height:

0.625 inches

Actuator Style:

Round

Actuator Diameter:

0.118 inches

Actuator Height:

0.413 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.000 amperes inductive dc and 3.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0