NSN 5930-00-201-8288

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-201-8288

Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Body Length:
1.940 inches
Body Width:
0.950 inches
Body Height:
0.687 inches
Switch Actuator Quantity:
1
Actuator Style:
Round
Actuator Diameter:
0.094 inches
Maximum Voltage Rating In Volts:
480.0 ac and 250.0 dc
Inclosure Type:
Uninclosed
Thready Qty Per Inch (tpi):
32
32 Thread Size:
Thread Size:
Thread Size: 0.138 inches
Thread Size: 0.138 inches Nonpile-up Contact Arrangement:
Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, momentary action single switch unit
Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, momentary action single switch unit Switch Release Force:
Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, momentary action single switch unit Switch Release Force: 10.0 ounces
Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, momentary action single switch unit Switch Release Force: 10.0 ounces Switch Actuating Force:
Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, momentary action single switch unit Switch Release Force: 10.0 ounces Switch Actuating Force: 30.0 ounces
Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, momentary action single switch unit Switch Release Force: 10.0 ounces Switch Actuating Force: 30.0 ounces Actuator Movement:
Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, momentary action single switch unit Switch Release Force: 10.0 ounces Switch Actuating Force: 30.0 ounces Actuator Movement: 0.010 overtravel inches
Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, momentary action single switch unit Switch Release Force: 10.0 ounces Switch Actuating Force: 30.0 ounces Actuator Movement: 0.010 overtravel inches Contact Load Current Rating At Maximum Rated Voltage:
Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, momentary action single switch unit Switch Release Force: 10.0 ounces Switch Actuating Force: 30.0 ounces Actuator Movement: 0.010 overtravel inches Contact Load Current Rating At Maximum Rated Voltage: 0.250 amperes resistive dc and 20.000 amperes resistive ac
Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, momentary action single switch unit Switch Release Force: 10.0 ounces Switch Actuating Force: 30.0 ounces Actuator Movement: 0.010 overtravel inches Contact Load Current Rating At Maximum Rated Voltage: 0.250 amperes resistive dc and 20.000 amperes resistive ac Thread Series Designator:
Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, momentary action single switch unit Switch Release Force: 10.0 ounces Switch Actuating Force: 30.0 ounces Actuator Movement: 0.010 overtravel inches Contact Load Current Rating At Maximum Rated Voltage: 0.250 amperes resistive dc and 20.000 amperes resistive ac Thread Series Designator: Unc
Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, momentary action single switch unit Switch Release Force: 10.0 ounces Switch Actuating Force: 30.0 ounces Actuator Movement: 0.010 overtravel inches Contact Load Current Rating At Maximum Rated Voltage: 0.250 amperes resistive dc and 20.000 amperes resistive ac Thread Series Designator: Unc Terminal Type And Quantity:
Thread Size: 0.138 inches Nonpile-up Contact Arrangement: 2 pole, single throw, normally open, momentary action single switch unit Switch Release Force: 10.0 ounces Switch Actuating Force: 30.0 ounces Actuator Movement: 0.010 overtravel inches Contact Load Current Rating At Maximum Rated Voltage: 0.250 amperes resistive dc and 20.000 amperes resistive ac Thread Series Designator: Unc Terminal Type And Quantity: 4 screw

-

NSN 5930-00-201-8288

Sensitive Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0