

View Online at <https://aerobasegroup.com/nsn/5930-00-201-8836>

Thread Class:

3a all threaded stud

Hazardous Locations/environmental Protection:

Dusttight

Overall Length:

3.875 inches

Body Length:

1.875 inches

Overall Diameter:

4.062 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between 40.0 degrees fahrenheit and 125.0 degrees fahrenheit

Mounting Method:

Threaded stud

Thready Qty Per Inch (tpi):

27 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

10.00 pounds per square inch gage

Thread Size:

0.500 inches all threaded stud

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+8.00/+40.00 actuation point inches of water and +5.00/+37.00 deactuation point inches of water

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

3.00 differential point inches of water

Contact Voltage Rating In Volts:

120.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0