

View Online at <https://aerobasegroup.com/nsn/5930-00-201-8836>

**Thread Class:**

3a all threaded stud

**Hazardous Locations/environmental Protection:**

Dusttight

**Overall Length:**

3.875 inches

**Body Length:**

1.875 inches

**Overall Diameter:**

4.062 inches

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between 40.0 degrees fahrenheit and 125.0 degrees fahrenheit

**Mounting Method:**

Threaded stud

**Thready Qty Per Inch (tpi):**

27 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

10.00 pounds per square inch gage

**Thread Size:**

0.500 inches all threaded stud

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

15.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+8.00/+40.00 actuation point inches of water and +5.00/+37.00 deactuation point inches of water

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Stimulus Rating:**

3.00 differential point inches of water

**Contact Voltage Rating In Volts:**

120.0 ac at sea level single voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Frequency In Hertz:**

60.0 single voltage

**Media For Which Designed:**

Liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0