NSN 5930-00-201-9309

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-201-9309

| view Online at https://acrobasegroup.com/nsi//0550-00-201-5505 |
|---|
| First Flat Length: |
| 0.438 inches single actuator |
| Flat Height: |
| 0.219 inches single actuator |
| Shaft Diameter: |
| 0.250 inches single actuator |
| Shaft Length: |
| 1.125 inches single actuator |
| Individual Section Quantity: |
| 2 |
| Knob Manufacturer Code: |
| 80064 |
| Knob Manufacturer Part Number: |
| 9-s-5401-l-1 |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 1 each section rear |
| Throw Quantity: |
| 2 each section rear |
| Mounting Facility Circle Radius: |
| 2.312 inches single mounting facility |
| Contact Voltage Rating In Volts: |
| 250.0 highest ac voltage rating at sea level |
| Mounting Facility Pattern: |
| Four position circular single mounting facility |
| Switch Actuator Indexing Position Quantity: |
| 4 single actuator |
| Shaft Type: |
| Round, flatted, threaded hole single actuator |
| Terminal Type: |
| Threaded stud |
| Contact Switching Action: |
| Breaks before makes each section rear |
| Switch Actuator Positioning Increment: |
| 90.0 degrees single actuator |
| Contact Load Current Rating: |
| 5.0 amperes resistive load highest ac voltage rating at sea level |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5930-00-201-9309

Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0