

View Online at <https://aerobasegroup.com/nsn/5930-00-201-9320>

Hazardous Locations/environmental Protection:

Explosion proof

First Flat Length:

0.625 inches single actuator

Flat Height:

0.312 inches single actuator

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

2.000 inches single actuator

Unthreaded Mounting Hole Diameter:

0.469 inches single mounting facility

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

3.781 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

3.781 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

1 each section rear

Contact Voltage Rating In Volts:

600.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Threaded stud

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

60.0 amperes resistive load ac at sea level

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0