

View Online at <https://aerobasegroup.com/nsn/5930-00-201-9351>

**Thread Length:**

0.500 inches single mounting facility

**Overall Length:**

2.188 inches

**Overall Width:**

1.500 inches

**First Flat Length:**

0.375 inches single actuator

**Flat Height:**

0.188 inches single actuator and 0.219 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.500 inches single actuator

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

0.625 inches 2nd mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Mounting Method:**

Threaded hole 2nd mounting facility

**Features Provided:**

Cam actuated

**Contact Voltage Rating In Volts:**

250.0 ac at sea level

**Mounting Facility Pattern:**

Two position in-line 2nd mounting facility

**Cam Actuated Switch Contact Arrangement:**

2 pole, double throw, both positions maintained each switch single section in-line

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section in-line

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

6.0 amperes resistive load dc at sea level

**Precious Material And Location:**

Contact surfaces silver and terminal surfaces silver

**Precious Material:**

Silver

**Style Designator:**

In-line, cam actuated

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0