NSN 5930-00-201-9589

Rotary Switch - Page 1 of 1



5930-00-201-9589

View Online at https://aerobasegrou	p.com/nsn/
Thread Length:	
0.375 inches single mounting facility	у
Shaft Diameter:	
0.250 inches single actuator	
Shaft Length:	
0.875 inches single actuator	
Individual Section Quantity:	
1	
Switch Contact Basic Design:	
Nonpile-up symmetrical	
Pole Quantity:	
1 single section rear	
Throw Quantity:	
2 single section rear	
Mounting Method:	
Threaded bushing single mounting f	acility
Thread Size:	
0.375 inches single mounting facility	,
Contact Voltage Rating In Volts:	
6.0 ac at sea level	
Switch Actuator Indexing Position	n Quantity:
Switch Actuator Indexing Position 2 single actuator	n Quantity:
_	n Quantity:
2 single actuator	n Quantity:
2 single actuator Shaft Type:	n Quantity:
2 single actuator Shaft Type: Round single actuator	n Quantity:
2 single actuator Shaft Type: Round single actuator Terminal Type:	n Quantity:
2 single actuator Shaft Type: Round single actuator Terminal Type: Tab, solder lug	
2 single actuator Shaft Type: Round single actuator Terminal Type: Tab, solder lug Contact Switching Action:	rear
2 single actuator Shaft Type: Round single actuator Terminal Type: Tab, solder lug Contact Switching Action: Makes before breaks single section	rear
2 single actuator Shaft Type: Round single actuator Terminal Type: Tab, solder lug Contact Switching Action: Makes before breaks single section Switch Actuator Positioning Incre	rear
2 single actuator Shaft Type: Round single actuator Terminal Type: Tab, solder lug Contact Switching Action: Makes before breaks single section Switch Actuator Positioning Incre 30.0 degrees single actuator	rear e ment:
2 single actuator Shaft Type: Round single actuator Terminal Type: Tab, solder lug Contact Switching Action: Makes before breaks single section Switch Actuator Positioning Incre 30.0 degrees single actuator Contact Load Current Rating:	rear e ment:
2 single actuator Shaft Type: Round single actuator Terminal Type: Tab, solder lug Contact Switching Action: Makes before breaks single section Switch Actuator Positioning Incre 30.0 degrees single actuator Contact Load Current Rating: 1.0 amperes resistive load ac at sea	rear e ment:
2 single actuator Shaft Type: Round single actuator Terminal Type: Tab, solder lug Contact Switching Action: Makes before breaks single section Switch Actuator Positioning Incre 30.0 degrees single actuator Contact Load Current Rating: 1.0 amperes resistive load ac at sea Thread Series Designator:	rear e ment:
2 single actuator Shaft Type: Round single actuator Terminal Type: Tab, solder lug Contact Switching Action: Makes before breaks single section Switch Actuator Positioning Incre 30.0 degrees single actuator Contact Load Current Rating: 1.0 amperes resistive load ac at sea Thread Series Designator: Unef single mounting facility	rear e ment:
2 single actuator Shaft Type: Round single actuator Terminal Type: Tab, solder lug Contact Switching Action: Makes before breaks single section Switch Actuator Positioning Incre 30.0 degrees single actuator Contact Load Current Rating: 1.0 amperes resistive load ac at sea Thread Series Designator: Unef single mounting facility Shelf Life:	rear e ment:
2 single actuator Shaft Type: Round single actuator Terminal Type: Tab, solder lug Contact Switching Action: Makes before breaks single section Switch Actuator Positioning Incre 30.0 degrees single actuator Contact Load Current Rating: 1.0 amperes resistive load ac at sea Thread Series Designator: Unef single mounting facility Shelf Life: N/a	rear e ment:
2 single actuator Shaft Type: Round single actuator Terminal Type: Tab, solder lug Contact Switching Action: Makes before breaks single section Switch Actuator Positioning Incre 30.0 degrees single actuator Contact Load Current Rating: 1.0 amperes resistive load ac at sea Thread Series Designator: Unef single mounting facility Shelf Life: N/a	rear e ment:
2 single actuator Shaft Type: Round single actuator Terminal Type: Tab, solder lug Contact Switching Action: Makes before breaks single section Switch Actuator Positioning Incre 30.0 degrees single actuator Contact Load Current Rating: 1.0 amperes resistive load ac at sea Thread Series Designator: Unef single mounting facility Shelf Life: N/a Unit Of Measure:	rear e ment:

Fiig:

A052b0