NSN 5930-00-201-9608

Rotary Switch - Page 1 of 2

Tab w/screw



View Online at https://aerobasegroup.com/nsn/5930-00-201-9608

| Hannadava Lagatiana/aminamantal Protestion | | | | | | |
|--|--|--|--|--|--|--|
| Hazardous Locations/environmental Protection: | | | | | | |
| Dustproof | | | | | | |
| Overall Length: | | | | | | |
| 8.062 inches | | | | | | |
| Overall Height: | | | | | | |
| 4.750 inches | | | | | | |
| Overall Width: | | | | | | |
| 4.750 inches | | | | | | |
| First Flat Length: | | | | | | |
| 0.750 inches single actuator | | | | | | |
| Flat Height: | | | | | | |
| 0.250 inches single actuator | | | | | | |
| Shaft Diameter: | | | | | | |
| 0.375 inches single actuator | | | | | | |
| Shaft Length: | | | | | | |
| 1.000 inches single actuator | | | | | | |
| Unthreaded Mounting Hole Diameter: | | | | | | |
| 0.406 inches single mounting facility and 0.410 inches single mounting facility | | | | | | |
| Individual Section Quantity: | | | | | | |
| 9 | | | | | | |
| Knob Manufacturer Part Number: | | | | | | |
| A | | | | | | |
| Switch Contact Basic Design: | | | | | | |
| Nonpile-up symmetrical | | | | | | |
| Pole Quantity: | | | | | | |
| 1 each section rear | | | | | | |
| Throw Quantity: | | | | | | |
| 1 each section rear | | | | | | |
| Mounting Method: | | | | | | |
| Unthreaded hole single mounting facility | | | | | | |
| Features Provided: | | | | | | |
| Actuator knob | | | | | | |
| Contact Voltage Rating In Volts: | | | | | | |
| 500.0 ac at sea level | | | | | | |
| | | | | | | |
| Mounting Facility Pattern: | | | | | | |
| Mounting Facility Pattern: Four position rectangular single mounting facility | | | | | | |
| | | | | | | |
| Four position rectangular single mounting facility | | | | | | |
| Four position rectangular single mounting facility Switch Actuator Indexing Position Quantity: | | | | | | |
| Four position rectangular single mounting facility Switch Actuator Indexing Position Quantity: 2 single actuator | | | | | | |

NSN 5930-00-201-9608

Rotary Switch - Page 2 of 2



| Con | tact | Swit | chino | ı Acti | on: |
|-----|------|------|-------|--------|------|
| | ıavı | OWIL | CHILL | ı Actı | vii. |

Makes before breaks each section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

30.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0