NSN 5930-00-201-9608

Rotary Switch - Page 1 of 2

Tab w/screw



View Online at https://aerobasegroup.com/nsn/5930-00-201-9608

Hazardous Locations/environmental Protection:					
Dustproof					
Overall Length:					
8.062 inches					
Overall Height:					
4.750 inches					
Overall Width:					
4.750 inches					
First Flat Length:					
0.750 inches single actuator					
Flat Height:					
0.250 inches single actuator					
Shaft Diameter:					
0.375 inches single actuator					
Shaft Length:					
1.000 inches single actuator					
Unthreaded Mounting Hole Diameter:					
0.406 inches single mounting facility and 0.410 inches single mounting facility					
Individual Section Quantity:					
9					
Knob Manufacturer Part Number:					
A					
Switch Contact Basic Design:					
Nonpile-up symmetrical					
Pole Quantity:					
1 each section rear					
Throw Quantity:					
1 each section rear					
Mounting Method:					
Unthreaded hole single mounting facility					
Features Provided:					
Actuator knob					
Contact Voltage Rating In Volts:					
500.0 ac at sea level					
Mounting Facility Pattern:					
Mounting Facility Pattern: Four position rectangular single mounting facility					
Four position rectangular single mounting facility					
Four position rectangular single mounting facility Switch Actuator Indexing Position Quantity:					
Four position rectangular single mounting facility Switch Actuator Indexing Position Quantity: 2 single actuator					

NSN 5930-00-201-9608

Rotary Switch - Page 2 of 2



Conta	ct Sv	vitchin	a Act	ion:
oonta	10L 01	V 1 L C 1 1 1 1 1	I ACL	IVII.

Makes before breaks each section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

30.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0