

View Online at <https://aerobasegroup.com/nsn/5930-00-201-9612>

**Body Style:**

Bushing/hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.998 inches and 1.002 inches

**Bushing Length:**

0.500 inches

**Body Length:**

1.937 inches

**Body Width:**

0.687 inches

**Body Height:**

0.812 inches

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Switch Actuator Quantity:**

1

**Actuator Style:**

Round

**Actuator Diameter:**

0.328 inches

**Actuator Free Position Height:**

1.500 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 230.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Actuator Movement:**

Between 0.040 pretravel inches and 0.219 overtravel inches and 0.007 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

300.000 milliamperes resistive dc and 30.000 milliamperes inductive dc and 300.000 milliamperes lamp dc and 30.000 milliamperes motor dc and 5.000 amperes resistive ac and 5.000 amperes motor ac

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0