

View Online at <https://aerobasegroup.com/nsn/5930-00-201-9612>

Body Style:

Bushing/hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.998 inches and 1.002 inches

Bushing Length:

0.500 inches

Body Length:

1.937 inches

Body Width:

0.687 inches

Body Height:

0.812 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Switch Actuator Quantity:

1

Actuator Style:

Round

Actuator Diameter:

0.328 inches

Actuator Free Position Height:

1.500 inches

Maximum Voltage Rating In Volts:

250.0 ac and 230.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Actuator Movement:

Between 0.040 pretravel inches and 0.219 overtravel inches and 0.007 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

300.000 milliamperes resistive dc and 30.000 milliamperes inductive dc and 300.000 milliamperes lamp dc and 30.000 milliamperes motor dc and 5.000 amperes resistive ac and 5.000 amperes motor ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0