

View Online at <https://aerobasegroup.com/nsn/5930-00-201-9884>

Thread Class:

2a single mounting facility

Thread Length:

0.500 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.031 inches

Overall Height:

2.250 inches

Overall Width:

1.125 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.375 inches single actuator

Nonturn Device Radius:

0.406 inches at 5: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Pin at 5: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Metallic inclosure and cam actuated

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

230.0 dc at sea level

Cam Actuated Switch Contact Arrangement:

2 pole, single throw, both positions maintained single switch single section in-line

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, fluted single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes single section in-line

Switch Actuator Positioning Increment:

62.5 degrees single actuator

Contact Load Current Rating:

20.0 amperes resistive load dc at sea level

Style Designator:

In-line, cam actuated

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0