

View Online at <https://aerobasegroup.com/nsn/5930-00-201-9885>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.500 inches single mounting facility

**Width Between Flats:**

0.188 inches single actuator and 0.219 inches single actuator

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

2.156 inches

**Overall Height:**

2.250 inches

**Overall Width:**

1.125 inches

**First Flat Length:**

0.438 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

1.000 inches single actuator

**Nonturn Device Radius:**

0.406 inches at 5: 00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Pin at 5: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Metallic inclosure and cam actuated

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

250.0 dc at sea level

**Cam Actuated Switch Contact Arrangement:**

2 pole, single throw, both positions maintained single switch single section in-line

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, parallel flatted single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes single section in-line

**Switch Actuator Positioning Increment:**

62.5 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

20.0 amperes resistive load dc at sea level

**Style Designator:**

In-line, cam actuated

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0