

View Online at <https://aerobasegroup.com/nsn/5930-00-202-1078>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Weatherproof and corrosion resistant

Overall Length:

74.440 inches

Overall Height:

1.000 inches

Overall Width:

1.000 inches

Case Material:

Metal

Actuator Style:

Adjustable arm

Actuator Diameter:

0.180 inches

Actuator Height:

1.240 inches

Actuator Width:

1.500 inches

Housing Diameter:

1.000 inches

Housing Length:

1.200 inches

Housing Bushing Length:

0.340 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

30.0 ounces

Switch Actuating Force:

48.0 ounces

Actuator Movement:

Between 20.0 pretravel degrees and 50.0 overtravel degrees and 4.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0