NSN 5930-00-202-1078

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-202-1078

g
Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Weatherproof and corrosion resistant
Overall Length:
74.440 inches
Overall Height:
1.000 inches
Overall Width:
1.000 inches
Case Material:
Metal
Actuator Style:
Adjustable arm
Actuator Diameter:
0.180 inches
Actuator Height:
1.240 inches
Actuator Width:
1.500 inches
Housing Diameter:
1.000 inches
Housing Length:
1.200 inches
Housing Bushing Length:
0.340 inches
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:
30.0 ounces
Switch Actuating Force:

48.0 ounces

NSN 5930-00-202-1078

Sensitive Switch - Page 2 of 2



Actuator Movement:

Between 20.0 pretravel degrees and 50.0 overtravel degrees and 4.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc and 5.000 amperes resistive ac and 5.000

amperes inductive ac	
Thread Series Designator:	

Uns

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0