NSN 5930-00-202-1078

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-202-1078

| g |
|---|
| Body Style: |
| Bushing mounted |
| Hazardous Locations/environmental Protection: |
| Weatherproof and corrosion resistant |
| Overall Length: |
| 74.440 inches |
| Overall Height: |
| 1.000 inches |
| Overall Width: |
| 1.000 inches |
| Case Material: |
| Metal |
| Actuator Style: |
| Adjustable arm |
| Actuator Diameter: |
| 0.180 inches |
| Actuator Height: |
| 1.240 inches |
| Actuator Width: |
| 1.500 inches |
| Housing Diameter: |
| 1.000 inches |
| Housing Length: |
| 1.200 inches |
| Housing Bushing Length: |
| 0.340 inches |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.469 inches |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, one position momentary single switch unit |
| Switch Release Force: |
| 30.0 ounces |
| Switch Actuating Force: |
| |

48.0 ounces

NSN 5930-00-202-1078

Sensitive Switch - Page 2 of 2



Actuator Movement:

Between 20.0 pretravel degrees and 50.0 overtravel degrees and 4.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc and 5.000 amperes resistive ac and 5.000

| amperes inductive ac | |
|---------------------------|--|
| Thread Series Designator: | |

Uns

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0