

View Online at <https://aerobasegroup.com/nsn/5930-00-203-4430>

Overall Length:

3.938 inches

Overall Height:

5.391 inches

Overall Width:

2.031 inches

Mounting Slot Width:

0.200 inches

Body Height:

3.203 inches

Unthreaded Mounting Hole Diameter:

0.200 inches

Capillary Tube Length:

72.0 inches

Bulb Length:

6.000 inches

Bulb Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

3.250 inches

Longest Vertical Distance Between Mounting Centers:

0.796 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Base and unthreaded hole and slot

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

6.9 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

-10.00/+55.00 actuation point degrees fahrenheit and -10.00/+55.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point knob with scale and external actuation point knob with scale

Contact Voltage Rating In Volts:

230.0 ac at sea level first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0